

VT8 LIGHT TOWER

VT8

The compact footprint and ease of use are two main features that make the VT8 light tower one of the top models in the Generac Mobile® range. High performance balanced with low cost allowed the VT8 to become the best-seller model in the extra-European market.



VT8 K3

VT8 Y3

VT8 P3

TECHNICAL DATA		VT8 K3	VT8 Y3	VT8 P3
Minimum dimensions (mm)	Length x Width x Height	2650 x 1300 x 2460	2650 x 1300 x 2460	2650 x 1300 x 2460
Maximum dimensions (mm)	Length x Width x Height	2650 x 2460 x 8000	2650 x 2460 x 8000	2650 x 2460 x 8000
Dry weight (kg)		719	719	719
Lifting system	M:Manual / H:Hydraulic	M	M	M
Mast rotation (°)		340	340	340
Lamps power (W)		4 x 1000	4 x 1000	4 x 1000
Lamps type	MH: MetalHalide / LD: LED	MH	MH	MH
Total lumen (Lm)		360000	360000	360000
Illuminated area (m²)		4200	4200	4200
Engine		Kubota D1105	Yanmar 3TN	Perkins 403D-11
Engine cooling	L: Liquid / A: Air	L	L	L
Cylinders (q.ty)		3	3	3
Engine speed (RPM)	50 / 60 Hz	1500 / 1800	1500 / 1800	1500 / 1800
Liquid containment (110%)	√:Yes / ●:No	●	●	●
Alternator	kVA/V/Hz	8/220/50 - 8/240/60	8/220/50 - 8/240/60	8/220/50 - 8/240/60
Outlet Socket	kVA/V/Hz	3/220/50 - 3/240/60	3/220/50 - 3/240/60	3/220/50 - 3/240/60
Avg. sound pressure	dB(A) @ 7m	68	68	68
Wind speed resistance (km/h)		110	110	110
Tank capacity (liters)		75	75	75
Total running time (h)		44	47	44

VT8 LIGHT TOWER

EN_CTS_VT8_1803_r2.5

THE BEST SELLER

The VT8 is the best seller model of light tower in the extra-european market, thanks to the vertical mast and the high quality features granted by Generac Mobile®

TOP STABILITY

Five fully integrated stabilizers will ensure maximum stability in every application.

VERTICAL MAST

A telescopic vertical mast with manual lifting system and a maximum height of 8 meters.

METAL HALIDE LAMPS

4x1000W powerful metal halide lamps able to illuminate medium and big working areas.

TRAILER OPTIONS

The VT8 is equipped as standard with a low speed trailer but it can be also mounted on a straight road trailer.

ENGINE OPTIONS

You can choose the engine you prefer between three options: Yanmar 3TN, Kubota D1105 and Perkins 403D-11



OPTIONS AVAILABLE

- Low speed site-tow trailer (standard)
- Road trailer type A (straight)
- Axle with torsion bar
- 110V sockets
- Pre-heating system
- Earth picket with 5m cable
- Main/generator selector switch
- Plastic box for documents
- Documents for EU road registration
- Dedicated colour
- Shut-off valve
- Certified spark arrestor
- Hot-dip zinc coating of mast sections
- Ball hitch type 50 mm
- Eyelet hitch type 50 mm
- Eco panel with digital timer and darkness sensor
- Liquid containment tray
- Schuko outlet socket (IP44)